



Version with Markings to  
Show Changes Made

APPLICATION FOR  
UNITED STATES OF AMERICA

\* \* \* \* \*

SPECIFICATION

5

TO ALL WHOM IT MAY CONCERN:

Be it known that We,

Francesco CAERAN  
Italian citizen  
of MONTEBELLUNA - ITALY

10

and

Alessandro POZZOBON  
Italian citizen  
of GIAVERA DEL MONTELLO - ITALY

have invented certain improvements in

15

"SPORTS SHOE"

20

of which the following description in connection with the  
accompanying drawings is a specification, like reference  
characters on the drawings indicating like parts in the several  
figures.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to a sports shoe such as ~~for example a ski boot, or a roller skate, or an ice skate,~~  
5 for example.

### 2. Description of the Related Art

Sports shoes ~~are currently in use which~~ are usually provided with a sole, with which a rigid or semirigid shell for containing the foot of the user is associated in an  
10 upward region.

A quarter is typically rotatably associated at the malleolar region and wraps around at least the lower portion of the leg.

Some sports shoes have a shell that is divided into a  
15 heel unit and a separate toe unit, so as to allow ~~to adjust the~~ length of the shoe to be adjusted.

For example, Swiss patent no. 611,495 is known that discloses a ski boot comprising a shell constituted by two separate parts that can slide on each other along a  
20 longitudinal axis.

The sliding interconnection between the two parts, i.e., between the heel unit and the toe unit of the shell, is ensured, proximate to the upper metatarsal region, by the presence of an extension that protrudes to the rear from the  
25 edge of the toe unit, so as to interact slidingly in a complementarily shaped seat provided proximate to the front edge of the heel unit.

At the lower surfaces of the toe unit and heel unit, their mutual sliding interconnection is achieved by arranging  
30 three pins, which protrude upward from the lower surface of the heel unit, in respective slots provided longitudinally in the lower surface of the toe unit.

In this manner, by moving the toe unit further forward

with respect to the heel unit, a corresponding increase in the length of the shoe is achieved.

The main drawback of this known type of sports shoe consists in that it allows to change the dimensions of the shoe  
5 only in a longitudinal direction.

However, a larger shoe size usually entails also an increase in the overall volume of the shoe, therefore both lengthwise and widthwise, and not only an increase in length.

Accordingly, an important drawback of these known types  
10 of sports shoes relates to the fact that they allow a comfortable fit only to users that have a preset foot size.

Another important drawback consists in that the prolonged use of a sports shoe that is excessively tight, for example in the metatarsal region, can cause a slowing in  
15 blood circulation, with consequent difficulty for the body to keep the foot warm.

In general, the known types of shoe cited above are difficult to adapt to the specific shape of the foot of the user, allowing comfortable use only at a specific size and  
20 thus compromising the possibility to fit feet of different sizes in the same shoes.

#### SUMMARY OF THE INVENTION

The aim of the present invention is therefore to  
25 solve the noted problems, eliminating the drawbacks of the cited known art, by providing a sports shoe that allows, as the size varies, an optimum adaptation of the overall volume of the shoe to the foot of the user.

Within this aim, an object of the present invention is  
30 to provide a sports shoe that allows to ensure maximum comfort of the user regardless of the dimensions of his foot, provided that they are within the size range covered by such shoe.

Another object of the present invention is to provide a

sports shoe that wraps around the foot so as to allow optimum blood circulation, therefore allowing the user to practice the sport in the best possible physical conditions.

5 Another object of the present invention is to provide a sports shoe that is structurally simple and has low manufacturing costs.

This aim and these and other objects that will become  
10 ~~better-more~~ apparent hereinafter are achieved by a sports shoe that comprises a sole that is rigidly associated with an upper shell, ~~that which~~ is divided into a heel unit and a separate toe unit, ~~characterized in that it.~~ The sports shoe also comprises adjusting means for increasing the overall volume of ~~said the~~ sports shoe by means of a forward movement of  
15 ~~said the~~ toe unit relative to the heel unit.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Further characteristics and advantages of the present invention will become ~~better-more~~ apparent from the following  
20 detailed description of an embodiment of the sports shoe according to the present invention, which is illustrated by way of a non-limitative example in the accompanying drawings, wherein:

Figure 1 is a partially sectional side view of a  
25 possible embodiment of the sports shoe according to the present invention;

Figures 2 and 3 are partially sectional plan views of the sports shoe of Figure 1, arranged in two different configurations, respectively with a small size and a large  
30 size.

In the examples of embodiments that follow, individual characteristics, given in relation to specific examples, may actually be interchanged with other different characteristics that exist in other examples of the embodiment.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to the ~~figures~~drawings, the reference numeral 1 designates a sports shoe, such as ~~for example~~ a ski boot, for example.

~~Sports~~The sports shoe 1 comprises a sole 2 that is monolithically associated with an upper shell 3, with which a quarter 4 that wraps around the lower part of the leg of the user is rotatably associated approximately at the malleolar region.

In the embodiment illustrated herein, the shell 3 is divided into a heel unit 5 and a separate toe unit 6, which partially overlap each other approximately at the metatarsal region of the foot.

The toe unit 6, constituted by a box-like body that is open at the rear and wraps around the tip of the foot of the user, has a first lower surface 7 in which there is, approximately along its longitudinal central axis, an approximately wedge-shaped slit 8.

Slit 8 affects, i.e. extends at, at least the region where ~~said the~~ toe unit 6 and ~~said the~~ heel unit 5 overlap, and preferably lies between the rear edge of the first lower surface 7 and the toe region of ~~said the~~ surface.

In this manner, the slit 8 forms, on ~~said the~~ first lower surface 7, two flat wings 9a and 9b, which are connected to each other proximate to the toe region.

Two first slots, respectively designated by the reference numerals 10a and 10b, are formed in the two wings 9a and 9b and are obtained along two directions that diverge toward the toe region.

Two protrusions 11a and 11b can be arranged in ~~said the~~ two slots 10a and 10b and protrude upward from a second lower surface, designated by the reference numeral 12, of ~~said the~~ heel unit 5.

Proximate to the toe region there are also two second slots 13 and third slots 14, which are formed respectively in the first lower surface 7 and in the second lower surface 12.

5 | ~~Said first and~~ The second and third slots 13 and 14,  
provided along axes that are approximately parallel to the longitudinal central axis of the shoe, approximately mutually overlap in pairs, and are connected in a downward region to two respective holes, generally designated by the reference numeral 15, formed in the sole 2.

10 | In particular, in the example shown in Figure 1, ~~said the~~  
holes 15 are formed approximately at right angles in a standardized toe block 16 that is associated with the toe unit 6 in a downward region.

The second slots 13 have, in a downward region, a  
15 | perimetric tang 13a for supporting, for example, a threaded nut, (not shown), which is suitable to interact with a complementarily threaded screw, (also not shown), which is arranged coaxially to the hole 15.

The nut and the screw, whose head abuts against a recess  
20 | 17 formed in a downward region with respect to the toe block 16, constitute means for temporarily locking the mutual sliding of the heel unit 5 and the toe unit 6.

In this manner, the first slots 10a and 10b, and the second and third slots 13 and 14, by interacting respectively  
25 | with the protrusions 11a and 11b and with the stem of ~~said~~ the screws, constitute elements for the mutual engagement and sliding of the toe unit 6 and the heel unit 5.

At the same time, the inclination with which ~~said the~~  
first slots 10a and 10b are provided, as well as the  
30 | presence of the slit 8, allow a gradual increase of the width of ~~said the~~ heel unit 5 when the toe unit 6 is moved forward.

Figures 2 and 3 illustrate the two extreme positions, respectively at the minimum size and at the maximum size, of the shoe 1; such figures show that the divarication of the

pair of wings 9a and 9b forces an equal divarication of the elastically deformable sides of the heel unit 5, at least proximate to the region of overlap with the toe unit 6.

It is therefore evident that the first slots 10a and 5 | 10b, together with the two wings 9a and 9b, constitute adjusting means for varying the overall volume of the sports shoe by moving ~~forward~~ the toe unit 6 forward with respect to the heel unit 5.

Use of the sports shoe is therefore as follows: with 10 | reference to Figure 1, in order to achieve size adjustment the user has to act on the locking screws, (not shown), by unscrewing them partially, so as to allow mutual sliding of the heel unit 5 and toe unit 6.

During this sliding, the movement of the protrusions 15 | along the first slots entails a divarication or a mutual approach of the two wings of the lower surface of the toe unit 6, accordingly entailing a variation of the width of the shoe.

In this manner, when the shoe is lengthened, it ~~the~~ 20 | shoe also widens proportionally, and vice versa.

Once the selected adjustment has been performed, the user can retighten the screws on the nuts.

It has thus been found that the present invention has achieved the intended aim and objects, a sports shoe having 25 | been devised which ~~allows to provide~~ provides, as the size varies, optimum adaptation of ~~said~~ the shoe to the foot of the user.

The present invention in fact allows ~~to adjust~~ 30 | simultaneously simultaneous adjustment both in the length and the width of the shoe, so as to vary its overall volume, ensuring a comfortable condition to the user regardless of the size selected.

The sports shoe therefore allows optimum blood circulation, allowing the user to ski always in the best

physical conditions.

Adjustment occurs simply and rapidly, and it is optionally possible to associate a graduated device for visualizing the adjustment made with the elements for mutual  
5 engagement and sliding between the heel unit and the toe unit.

The present invention is, of course, susceptible ~~of~~ to numerous modifications and variations, all of which are within the scope of the appended claims.

10 Thus, for example, it is possible to provide a sports shoe in which the first slots 1 0a, 1 0b are provided in the lower surface 7 of the heel unit 5 and the protrusions 11 a, 11 b protrude below the lower surface of the toe unit 6.

As an alternative to the provision of the first slots,  
15 it is possible to provide, in the lower surface of the heel unit, a pair of slots that diverge appropriately toward the toe region.

Another embodiment provides for two or more slits along the lower surface of the toe unit; as an alternative,  
20 one might provide a toe unit that has a lower surface at least partially made of an elastically deformable material.

The materials used, as well as the dimensions that constitute the individual components of the present invention, may of course be more pertinent according to  
25 specific requirements.

The various means set forth in the above description for performing certain different 'functions need not certainly coexist only in the illustrated embodiment but can be present per se in different shoe embodiments, with size  
30 adaptation provisions.

The disclosures in Italian Patent Application No. TV2002A000149, from which ~~this~~ the present application claims priority, are incorporated herein by reference.

ABSTRACT OF THE DISCLOSURE

A sports shoe ~~comprising~~ includes a sole on which a shell divided into a heel unit and a separate toe unit is associated, ~~the~~ The heel unit and the toe unit are  
5 mutually associated so that they can slide along a substantially longitudinal axis and ~~comprise~~ include an adjustment device for increasing the overall volume of the sports shoe by means of a forward movement of the toe unit.